

Modlink MSDD front panel interface Data connector insert

RJ45; RJ12; USB; USB (form A)

1 x RJ45, 8-pole metal, CAT5e (female/female); 1 x RJ12, 6-pole plastic; 2 x USB- (female/female) form A

Image**Approvals****Technical Data**

Nominal voltage	SUB-D: max. 125 V AC/150 V DC; RJ4: max. 48 V AC/DC; RJ12: max. 48 V AC/DC; USB: max. 30 V AC/DC; PS2: max. 30 V AC/DC; DVI: max. 40 V AC
Nominal current	SUB-D: max. 3 A; RJ45: max. 1 A; RJ12: max. 1 A; USB: max. 1 A; PS2: max. 1 A; DVI: max. 1.5 A
Wire diameter	SUB-D: max. 0.5 mm ² /AWG 20; PS2: max. 0.22 mm ² /AWG 24
Fixing	SUB-D: UNC 4...40 bolt; RJ45: staple; RJ12: staple; USB: snap-in; PS2: snap-in
Specification	SUB-D: (DIN 41652/IEC807); RJ45: CAT5e (100 MHz or Mbit/s); USB: 2.0/Type 2dB (max. 480 Mbit/s)
Mounting depth mounted	SUB-D: approx. 32 mm; RJ45: approx. 32 mm; RJ12: approx. 32 mm; USB: approx. 80 mm; PS2: approx. 32 mm

General data

Shielded	yes
----------	-----

Commercial data

Gross weight	63,000
Net weight	63,000
Weight unit	Gramm
Basic unit	ST
Customs tariff number	85369010
Unit (piece)	1,000
Limited value	1,000